

This article is available online at:

<http://www.cybernetman.com//kb/index.cfm/fuseaction/home.viewArticles/articleId/98>

What are the specs for the i-One M661S/T?

Product specifications and system diagram

HARDWARE

CPU

- Intel Pentium-IV (up to 3 GHz) / Celeron (up to 2.8 GHz) processor
- Socket 478 type
- System Bus(FSB) : 800/533/400 MHz
- L2 Cache : 128 KB (Celeron) / 512 KB (P-IV)

Chipset

- SiS M661FX(North bridge) + SiS 963(South bridge)

System Memory

- DIMM x 2 (up to 2 GB)
- DDR400/333/266/200

System BIOS

- Award BIOS : ACPI 1.0b & USB-FDD Booting Support

Display

- Built-in 17" TFT-LCD Display Monitor (1280x1024, LVDS Interface)
- SXGA TFT LCD
- Contrast ratio: 500: 1(typ)
- white luminance: 300(typ)
- pixel H x V 1280x1024
- Surface Treatment: Hard coating (3H), anti-glare treatment
- Screen Diagonal 432(17")
- active area: 337.920x270.36
- optical rise time/fall time: 8 ms
- color saturation: 72% NTSC
- Power consumption: 25.8 w
- electrical interface: dual channel LVDS
- ROHS compliance.
- Integrated SiS 315 graphic core
- VGA Out : UXGA(1600x1200) Support
- Shared VGA Memory(16~128 MB) with System Memory
- 2D & 3D Graphics Support
- TV-Out (Composite Video) Support

Audio

- AC'97 v2.2 compliant (RealTek ALC201)
- 16bit Stereo Sound
- Built-in 2 Speakers (3W/3W, total 6W)

Storage

- HDD : 3.5" size, Ultra ATA/100/133 (up to 160 GB)
- Integrated Slim CD-ROM drive: Optional DVD-ROM & Combo(DVD &

CD-RW) drive

Input / Output / Peripherals

- PS/2 Keyboard and Mouse port
- Two Serial RS-232C port (1 Internal port for Touch screen support)
- One DB-25F Parallel port
- Microphone in / Speaker out / Line in
- One RJ-45 Ethernet connector
- Four USB port (USB v2.0 compliant)
- One IEEE 1394 port
- One VGA Out
- TV-Out : Composite Video(default)
- TV Cable In (optional)
- Touch screen (optional)

Networking

- TCP/IP, 10/100/1000 Base-T Fast Ethernet
- Built-in Ethernet Controller: RealTek® RTL8100C/RTL8110S

Operating System

- Microsoft Windows XP Home / Professional Edition

BIOS Utility Program

- Hardware monitoring utility (CPU Temperature & Voltage, Fan Speed, System voltage)

Environmental Specifications

- Operating temperature 5° to 35°C
- Storage temperature 0° to 60°C
- Humidity 30% to 80% non-condensing

Power Specifications

- AC to DC adapter
- 100-240 VAC at 50-60Hz
- Max 150W

Dimensions

- **LENGTH** 14.5"
- **WIDTH** 15.5"
- **DEPTH** 3.5"
- **WEIGHT (NO BASE)** 14.5 lbs
- **WEIGHT (w/ BASE)** 19.6 lbs
- **MOUNTING SCREW** 100mm x 100mm
- **SCREW RECESS DEPTH** 5mm

Once removed from its pedestal stand the i-One can be mounted on a wall arm. Its back mounting plate is a standard VESA 100 mm by 100 mm configuration.

There is a 5mm step down area of 120mm x 120mm around the VESA mounting.

Display width – 39.2 cm / 15.5 inch

Display depth – 9 cm / 3.54 inch

(Exact dimensions of viewable screen 13.25" wide 10.6" high)

Display height without stand – 36.5 cm / 14.5 inch

Display height on pedestal – 44.45 cm / 17.5 inches

i-One Base dimension; 26cm deep, 28cm wide (front), 22cm wide (back).