



CYBERMED H19 19" Medical Grade All-in-One PC



Display	<ul style="list-style-type: none"> • 19-inch LCD (1280x1024) 	Security Lock	<ul style="list-style-type: none"> • Security lock slot located on the back of the case
CPU Support	<ul style="list-style-type: none"> • Intel Core i3, i5 & i7 processors 	Wall Mount	<ul style="list-style-type: none"> • Supports 75mm & 100mm VESA mounting holes
I/O Ports	<ul style="list-style-type: none"> • 2x USB 3.0 Ports, 4x USB 2.0 ports • 1x RS232, option to expand to 5 COM ports • DVI-I Monitor Out Port • HDMI Full 1080p 	HDD Support	<ul style="list-style-type: none"> • Integrated Serial ATA controller facilitates high-speed transfers up to 3Gbps for each of the four ports
Chipset	<ul style="list-style-type: none"> • Intel H61 Express chipset (Sandy Bridge) 	Expansion Slots	<ul style="list-style-type: none"> • Two Mini PCI-e (1x Full-Size and 1x Half-Size)
Bios	<ul style="list-style-type: none"> • AMI Flash BIOS supports ACPI, API, DMI, Plug & Play, and security password. Supports booting from HDD, PXE, LAN, CD-ROM, and ANY USB device. Has BIOS System POST and BIOS setup password protection. 	Audio	<ul style="list-style-type: none"> • Realtek ALC892 High Definition Audio enables premium Dolby Digital 5.1 surround sound, 10 channels of enhanced sound quality, and delivers advanced features such as multiple audio streams and jack re-tasking.
Operating System	<ul style="list-style-type: none"> • Windows 7, Windows 8, Linux 	Weight	<ul style="list-style-type: none"> • 18.1 lbs
Video & Graphics	<ul style="list-style-type: none"> • Intel HD Graphics, Optional NVIDIA GeForce GT630M GPU with 1GB DDR 	Dimensions	<ul style="list-style-type: none"> • 17" x 15.8" x 3.2" (L, W, D)
Networking	<ul style="list-style-type: none"> • Dual Gigabit (Gbe) Fast Ethernet, Realtek RTL 8111E 	Colors	<ul style="list-style-type: none"> • White with Antimicrobial Germ Protection
Power Supply	<ul style="list-style-type: none"> • 135 Watt Medical Grade Adapter 100 ~ 240V AC, 50-60Hz. Supports Output range: DC12V/19V. 5.0A/9.5A Adapters for Energy Star 5.0/UL 	Memory	<ul style="list-style-type: none"> • 2 x DDR3 204-pin SO-DIMM sockets, populated up to 8GB Max. Supports PC3-10600 1333MHz SO-DIMM
Environment	<ul style="list-style-type: none"> • Ambient Temperature: 0°C ~ 50°C (operating) 	Relative Humidity	<ul style="list-style-type: none"> • 10% ~ 90% (non-condensing)
Touch Screen	<ul style="list-style-type: none"> • 5-Wire Resistive Single Touch 	Certifications	<ul style="list-style-type: none"> • EN60601-1, FCC CLASS B, CE, UL60950, ES 5.2, RoHS, WEEE, IP64 Front Bezel Waterproof
Wireless	<ul style="list-style-type: none"> • Intel Centrino 802.11 agn, 2x2, dual band delivers up to 300 Mbps speed, Bluetooth 4.0 	Swivel Base	<ul style="list-style-type: none"> • Optional base enables left/right rotation up to 60°. Tilt from -5 to 60°.