



DISPLAY & TOUCH	18.5-inch 16:9 widescreen (1400x787), 5-Wire resistive touch
CPU SUPPORT	Intel® Core™ 2 Duo, Intel® Core™ 2 Quad @ 1333MHz FSB LGA775 up to 95W. Intel® Pentium® D Processors with Hyper-Threading Technology, Intel® Celeron® D processor, supports 1.3GHz - 3.4GHz 1333/1066/800MHz System Bus. Supports 9x, 5x and 6x series processors with EM64T
CHIPSET	Eaglelake: Intel® G45 Express Chipset, Intel® ICH10 chipset
MEMORY	2 x DDR3 204-pin SO-DIMM sockets, populated up to 8GB. Supports PC3-10600 1333MHz SO-DIMM
HDD SUPPORT	Integrated Serial ATA controller facilitates high-speed transfers up to 3Gbps for each of the four ports. Supports upgrades or expansion of hard drives and new SATA optical drives. 2 x SATA2 ports
VIDEO & GRAPHICS	The Intel® G45 Express Chipset, with Intel® Graphics Media Accelerator X4500HD (Intel® GMA X4500HD), includes built-in support for full 1080p high-definition video playback, including Blu-ray* disc movies. This powerful video engine provides users with a rich, new media experience to deliver smooth HD playback without the need for add-in video cards or decoders. Intel® GMA X4500HD comes with Intel® Clear Video Technology, a combination of video processing hardware and software technologies designed to enhance the visual experience. In addition to video, the Intel® G45 Express Chipset delivers optimized 3D graphics performance and support for Microsoft DirectX* 10, Shader Model* 4.0 and OpenGL* 2.0. Dynamic Video Memory(DVMT) allocated as needed from 128MB to 1759MB
NETWORKING	1 x Gigabit (GbE) Fast Ethernet, using Realtek RTL 8111DL
AUDIO	Realtek AL889 High Definition Audio enables premium Dolby Digital 5.1 surround sound, 10 channels of enhanced sound quality, and delivers advanced features such as multiple audio streams and jack re-tasking. Audio is fully compliant with the Azalia 1.0 specification. Two built-in 2.5 watt stereo speakers with three audio jacks for Audio Out, Line-in, and Microphone
I/O PORTS	6 x USB 2.0 Ports with transfer rate of 480Mbps, 2 x RS-232 Serial Ports, 1 x DVI-I
WALL MOUNT	Supports both 75mm and 100mm VESA mounting holes
OPTICAL DRIVE	One slim type Optical Drive, DVD+/-RW or Blu-ray

EXPANSION SLOTS	One Mini PCI Two Mini PCI-e
SYSTEM BIOS	Award Flash BIOS supports ACPI, API, DMI, Plug & Play, and security password. Supports booting from HDD, PXE, LAN, CD-ROM, and any USB device
BIOS SECURITY	Award BIOS System POST and BIOS setup password protection
POWER SUPPLY	Uses 180Watt AC Adapter. Input: universal 100 ~ 240V AC, 50-60Hz. Output: 19V DC, 9.48A. Controlled by Dual Mode Power button on the keyboard. Low power sleep mode saves energy
SECURITY LOCK	Security lock slot located on the back of the system case
WEIGHT	Unit: 23.3lbs with base, 15.7lbs without base, Power Adapter: 1.7lbs
OPERATING ENVIRONMENT	Ambient Temperature: 0°C ~ 50°C (operating)
RELATIVE HUMIDITY	10% ~ 90% (non-condensing)
OPERATING SYSTEM	Microsoft Windows 7, Vista, XP, 2000, Linux
DIMENSIONS	19.3" long, 14.2" tall, 3.1" deep (not including base)
AVAILABLE COLOR	Black
SAFETY & EMI CERTIFICATIONS	FCC Class B, CE, UL60950, Energy Star 5.0, EPEAT Gold rated, RoHS, WEEE

Corporate Headquarters
Cybernet Manufacturing
5 Holland, Buildings 201 & 205
Irvine, CA 92618
Toll free: 888-834-4577
Local: 949-600-8000
Fax: 949-600-8013
www.cybernetman.com
sales@cybernetman.com
support@cybernetman.com

Cybernet Europe
Network House, Hawkins Road
Colchester, Essex CO2 8LA
United Kingdom
UK Phone: 0845-539-1200
UK Fax: 0845-539-1201
www.cyberneteuropa.com
sales@cyberneteuropa.com
support@cyberneteuropa.com

Space Technology Co., Ltd.
4F, No 49, Lane 76, Rui Guang Rd.
NeiHu District, Taipei, Taiwan, R.O.C.
Tel: 886-2-2790-4776
Fax: 886-2-2793-3172
www.cybernet.com.tw
sales@cybernet.com.tw
support@cybernet.com.tw