



MEDICAL MONITORS 22" & 24" Medical Grade Displays



	22" Medical Monitor	24" Medical Monitor	
Display	• 22" medical grade 16:9 LED (1920x1080)	• 23.6" medical grade 16:9 LED (1920x1080)	
Weight	• 14.40 lbs	• 16.80 lbs	
Dimensions	• 21.75" x 14.5"x 2.3" (L, W, D)	• 23.5" x 14.8"x 2.08" (L, W, D)	
Power Supply	• 120W Medical Grade Power Supply, Input: universal 100 ~ 240V AC, 50-60Hz. Supports Output range: DC18V-19V. 7.5A Adapters for Energy Star 6.0/UL		
I/O Ports	• 1x HDMI Input, 1x USB Input (for touchscreen), 1x Power Input (see above)		
Wall Mount	• Supports 75mm & 100mm VESA mounting holes		
Touch Screen	PCAP Multi Touch (Antiglare Technology optional)		
Waterproof	● IP65 Front Bezel and IPX1 Back Cover		
Environment	• Ambient Temperature: 0°C ~ 40°C (operating)		

40% Sodium Hydroxide Acetone

Carbitol Acetetate

Certifications

Cellosolve Acetetate

Ethonal -Alcohol

Methylene Chloride

Hydrochloric Acid 6%

Isopropanol (Isopropyl Alcohol) / Propanol

Methyl Ethyl Ketone

Heptane

Toluene

Turpentine

VM & P Naptha

Bleach (Sodium Hypochlorite, NaOCI)

Benzyl Alcohol Hydrogen Peroxide

R	esu	lt

Damage

Damage

Damage

Damage

500g load with 95% Alcohol | (OK up to 6000 times of cleaning)

• EN60601-1, UL60950 electrical safety, FCC class B, CE, Energy Star 6.1, RoHS 2

Damage Damage

Damage

Damage* | (OK up to 6000 times of cleaning)

Damage

Damage

500g load with 5% Cresol | (OK up to 6000 times cleaning)

Damage

500g load with 10% Bleach | (OK up to 6000 times cleaning)

Damage

Damage

Touch Glass Safe Cleaning Chemicals List

OK 40% Sodium Hydroxide ОК Carbitol Acetetate OK

Cellosolve Acetetate Ethonal -Alcohol Methylene Chloride

Acetone

Hydrochloric Acid 6% Sulfuric Acid 70% Nitric Acid 40%

Hexane Isopropanol (Isopropyl Alcohol) / Propanol

Methyl Ethyl Ketone Heptane

Toluene Turpentine

VM & P Naptha Bleach (Sodium Hypochlorite, NaOCI)

Benzyl Alcohol Hydrogen Peroxide

ОК OK OK ОК OK Damage OK ОК ОК ОК Damage OK ОК Damage Damage

Result