




ZPC H6 All-in-One Keyboard PC



| | | | |
|-----------------------------|---|--------------------------|--|
| Display | <ul style="list-style-type: none"> • 1080p Dual Monitor Capability, VGA and HDMI, 1400x787 HD | LED Indicators | <ul style="list-style-type: none"> • Power LED, HDD Status Indicator, Scroll Lock, Num Lock, Caps Lock |
| CPU Support | <ul style="list-style-type: none"> • Intel Core i5/i3/Pentium/Celeron, 5 GT/s System Bus, 1155-pin socket up to 35W. Intel® Sandy Bridge Processor | Hotkeys | <ul style="list-style-type: none"> • N/A |
| I/O Ports | <ul style="list-style-type: none"> • 2x USB 3.0 ports, 2x USB 2.0 ports • 1x RS232 serial port • 1x HDMI port • 1x LAN RJ-45 Jack • 1x Audio Jack (Line-Out & Microphone) • 1x S/PDIF Connector • 1x DC/IN port • 1x TV-Tuner port (Optional) with 1x RCA Jack + Coax Cable • 1x Kensington Lock | Audio | <ul style="list-style-type: none"> • Realtek ALC661 High Definition Audio enables premium Dolby Digital 5.1 surround sound and delivers advanced features such as multiple audio streams and jack re-tasking. Two built-in 1.5watt stereo speakers with two audio jacks for Audio Out and Microphone. |
| Chipset | <ul style="list-style-type: none"> • Intel H61 Express Chipset | Optical Drive | <ul style="list-style-type: none"> • One slim type Optical Drive, DVD+/-RW or Blu-ray |
| Memory | <ul style="list-style-type: none"> • 2 x DDR3 1066/1333 MHz SO-DIMM sockets, populated up to 8GB Max | HDD Support | <ul style="list-style-type: none"> • 1x 2.5" SATA or Solid State Drive |
| Operating System | <ul style="list-style-type: none"> • Windows 8, Windows 7, XP, Linux | Weight | <ul style="list-style-type: none"> • 5.07 lbs |
| Video & Graphics | <ul style="list-style-type: none"> • Intel HD Graphics | Touchpad | <ul style="list-style-type: none"> • N/A |
| Networking | <ul style="list-style-type: none"> • 1x 10/100/1000MB Fast Ethernet, using Realtek RTL8111E | Power Supply | <ul style="list-style-type: none"> • Uses 120 Watt Power Adapter, AC. Input: 100~240V AC, 1A, 50-60Hz. DC Output: 19V, 6.32A. |
| Bios | <ul style="list-style-type: none"> • AMI Flash BIOS supports ACPI, API, DMI, Plug & Play, and security password. Supports booting from HDD, PXE, LAN, CD-ROM, and any USB device. Has BIOS System POST and BIOS setup password protection. | Relative Humidity | <ul style="list-style-type: none"> • 10% ~ 90% (non-condensing) |
| Environment | <ul style="list-style-type: none"> • Ambient Temperature: 0°C ~ 50°C (operating) | Dimensions | <ul style="list-style-type: none"> • 18.31" x 7.6" x 1.3" (L, W, D) |
| Expansion Slots | <ul style="list-style-type: none"> • 2x Mini PCI-e (1x Full-Size and 1x Half-Size) | Certifications | <ul style="list-style-type: none"> • FCC Class B, CE, CCC, RoHs |
| Keyboard | <ul style="list-style-type: none"> • Standard 104-Key U.S. Keyboard | Colors | <ul style="list-style-type: none"> • Black |