



IPOS H19 All-in-One POS System



| | | | |
|-----------------------------|---|--------------------------|--|
| Display | <ul style="list-style-type: none"> • 19-inch LCD (1280x1024) | Webcam | <ul style="list-style-type: none"> • Optional 1.3 Megapixel Camera |
| CPU Support | <ul style="list-style-type: none"> • Intel Core i3, i5 & i7 processors | Wall Mount | <ul style="list-style-type: none"> • Supports 75mm & 100mm VESA mounting holes |
| I/O Ports | <ul style="list-style-type: none"> • 2x USB 3.0 Ports, 4x USB 2.0 ports • 1x RS232, option to expand to 5 COM ports • DVI-I Monitor Out Port • HDMI Full 1080p | Audio | <ul style="list-style-type: none"> • Realtek ALC892 High Definition Audio enables premium Dolby Digital 5.1 surround sound, 10 channels of enhanced sound quality, and delivers advanced features such as multiple audio streams and jack re-tasking. |
| Chipset | <ul style="list-style-type: none"> • Intel H61 Express chipset (Sandy Bridge) | Expansion Slots | <ul style="list-style-type: none"> • Two Mini PCI-e (1x Full-Size and 1x Half-Size) |
| Bios | <ul style="list-style-type: none"> • AMI Flash BIOS supports ACPI, API, DMI, Plug & Play, and security password. Supports booting from HDD, PXE, LAN, CD-ROM, and ANY USB device. Has BIOS System POST and BIOS setup password protection. | Power Supply | <ul style="list-style-type: none"> • 120Watt AC Adapter. Input: universal 100 ~ 240V AC, 50-60Hz. Supports Output range: DC12V/19V. 5.0A/9.5A Adapters for Energy Star 6.0/UL |
| Operating System | <ul style="list-style-type: none"> • Windows 10, Windows 8, Windows 7, Linux | Weight | <ul style="list-style-type: none"> • 16.5 lbs |
| Video & Graphics | <ul style="list-style-type: none"> • Intel HD Graphics, Optional NVIDIA GeForce GT720M GPU with 2GB DDR | Dimensions | <ul style="list-style-type: none"> • 17" x 15.8" x 3.2" (L, W, D) |
| Networking | <ul style="list-style-type: none"> • Dual Gigabit (Gbe) Fast Ethernet, Realtek RTL 8111E | Colors | <ul style="list-style-type: none"> • Black |
| Certifications | <ul style="list-style-type: none"> • UL60950 electrical safety, FCC class B, CE, Energy Star 6.0, RoHs 2.0, WEE | Memory | <ul style="list-style-type: none"> • 2 x DDR3 204-pin SO-DIMM sockets, populated up to 8GB Max. Supports PC3-10600 1333MHz SO-DIMM |
| Environment | <ul style="list-style-type: none"> • Ambient Temperature: 0°C ~ 50°C (operating) | Relative Humidity | <ul style="list-style-type: none"> • 10% ~ 90% (non-condensing) |
| Touch Screen | <ul style="list-style-type: none"> • 5-Wire Resistive Single Touch | HDD Support | <ul style="list-style-type: none"> • Integrated Serial ATA controller facilitates high-speed transfers up to 3Gbps for each of the four ports |
| Wireless | <ul style="list-style-type: none"> • 802.11 b/g/n + Bluetooth 4.0 | Swivel Base | <ul style="list-style-type: none"> • System base enables left/right rotation up to 60°. Tilt from -5 to 60°. |
| Security Lock | <ul style="list-style-type: none"> • Security lock slot located on the back of the case | Certifications | <ul style="list-style-type: none"> • FCC Class B, CE, UL60950, Energy Star 6.0, RoHS 2.0, WEEE |